

Technical Specifications

InRow RC, 300mm, Chilled Water, 208-230V, 50/60Hz - HT | ACRC301H | Downloaded on 02/17/2021 (EST)



InRow RC, 300mm, Chilled Water, 208-230V, 50/60Hz - HT

ACRC301H

Call for More Information +855-23-964-311

- Includes: Installation guide, Operations and maintenance manual

Input	
Input frequency	50/60 Hz
Input Connections	Hard wire 3-wire
Number of Power Cords	2
Power Feeds	2.0
Input Power	1900 Watts
Maximum Overcurrent Protection	15.0A
Minimum Circuit Amp Capacity	15.0

Communications & Management	
Control panel	Multifunction LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity

Physical	
Maximum Height	1991MM, 199.1CM
Maximum Width	300MM, 30.0CM
Maximum Depth	1095MM, 109.5CM
Rack Height	42U
Net Weight	210.0KG
Shipping weight	220.0KG
Shipping Height	2118MM, 211.8CM
Shipping Width	746MM, 74.6CM
Shipping Depth	1137MM, 113.7CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Color	Black
Units per Pallet	1.0

Conformance	
Approvals	C-Tick, CE, EN 55022 class A, EN 55024, EN 60950, GOST, IEC 60950, IEC 61000-3-2, IEC 61000-3-3, MEA, VDE
Standard warranty	1 year (parts only)

Sustainable Offer Status	
RoHS	Compliant
Proposition 65 Warning	Available in Documentation tab

General	
Air Discharge Patterns	Horizontal
Air Flow	1982.18lps
Intake Air	Rear return
Minimum Water Inlet Temperature	7.0 °C

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.