

## Technical Specifications

InRow RC, 300mm, Chilled Water, 100-240V, 50/60 Hz - ST w/ gravity drain | ACRC301SX797 | Downloaded on 02/17/2021 (EST)



# InRow RC, 300mm, Chilled Water, 100-240V, 50/60 Hz - ST w/ gravity drain

ACRC301SX797

Call for More Information +855-23-964-311

- Includes: Installation guide, Operations and maintenance manual

Input	
Input frequency	50/60 Hz
Input Connections	IEC 60309 16 A 2P + E, NEMA L5-20P
Number of Power Cords	2
Power Feeds	2.0
Input Power	800 Watts

Communications & Management	
Control panel	Multifunction LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity

Physical	
Maximum Height	1991MM, 199.1CM
Maximum Width	300MM, 30.0CM
Maximum Depth	1095MM, 109.5CM
Rack Height	42U
Net Weight	184.0KG
Shipping weight	192.0KG
Shipping Height	2118MM, 211.8CM
Shipping Width	746MM, 74.6CM
Shipping Depth	1137MM, 113.7CM
Color	Black
Units per Pallet	1.0

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Conformance	
Approvals	C-Tick, CE, EN 55022 class A, EN 55024, EN 60950, GOST, IEC 60950, IEC 61000-3-2, IEC 61000-3-3, MEA, VDE
Standard warranty	1 year (parts only)

  

General	
Air Discharge Patterns	Horizontal
Air Flow	1510.23lps
Intake Air	Rear return
Minimum Water Inlet Temperature	7.0 °C

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.