



InRow RC, 600mm, Chilled Water, 380-415V, 50/60Hz

ACRC602

Call for More Information +855-23-964-311

- Includes: Installation guide, Operations and maintenance manual

Input	
Input frequency	50/60 Hz
Input Connections	IEC 60309 16 A 3P + N + PE
Number of Power Cords	2

Communications & Management	
Control panel	Multifunction LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity

Physical	
Maximum Height	1991MM, 199.1CM
Maximum Width	600MM, 60.0CM
Maximum Depth	1070MM, 107.0CM
Rack Height	42U
Net Weight	345.45KG
Shipping weight	405.45KG
Shipping Height	2166MM, 216.6CM
Shipping Width	850MM, 85.0CM
Shipping Depth	1137MM, 113.7CM
Color	Black
Units per Pallet	1.0

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Conformance	
Approvals	CE, CUL listed, Industry Canada, UL listed, VDE
Standard warranty	1 year (parts only), 1 year on-site repair or replace with factory authorized Start-Up

General	
Air Discharge Patterns	Horizontal
Air Flow	2831.68lps
Condensate Pump Capacity	0.01lps
Intake Air	Rear return
Minimum Water Inlet Temperature	7.0 °C

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.