



InRow RC, 600mm, Chilled Water 380-415V 50/60 Hz, w/ humidifier

ACRC602P

Call for More Information +855-23-964-311

- Includes: Installation guide, Operations and maintenance manual

Input	
Input frequency	50 Hz +/- 3 Hz
Input Connections	Hard wire 4-wire (3P + E)
Number of Power Cords	2
Input Power	15000 Watts

Communications & Management	
Control panel	Multifunction LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity

Physical	
Maximum Height	1991MM, 199.1CM
Maximum Width	600MM, 60.0CM
Maximum Depth	1070MM, 107.0CM
Rack Height	42U
Net Weight	352.73KG
Shipping weight	463.18KG
Shipping Height	2166MM, 216.6CM
Shipping Width	850MM, 85.0CM
Shipping Depth	1137MM, 113.7CM
Color	Black
Units per Pallet	1.0

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Conformance	
Approvals	CUL listed, FCC part 15 class A, GOST, Industry Canada
Standard warranty	1 year (parts only), 1 year on-site repair or replace with factory authorized Start-Up

General	
Air Discharge Patterns	Horizontal
Air Flow	2831.68lps
Condensate Pump Capacity	0.01lps
Humidification Value	6.59pounds/hour
Intake Air	Rear return
Minimum Water Inlet Temperature	7.0 °C

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.