



## InRow RD, 300mm, Air Cooled, 220-240V, 50Hz ACRD101

Call for More Information +855-23-964-311

- Includes: Installation guide, Operations and maintenance manual

### Input

Input frequency	50 Hz
Input Power	4400 Watts

### Communications & Management

Control panel	Multifunction LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity

### Physical

Maximum Height	1991MM, 199.1CM
Maximum Width	300MM, 30.0CM
Maximum Depth	1070MM, 107.0CM
Rack Height	42U
Net Weight	183.64KG
Shipping weight	221.82KG
Shipping Height	2118MM, 211.8CM
Shipping Width	746MM, 74.6CM
Shipping Depth	1137MM, 113.7CM
Color	Black
Units per Pallet	1.0

### Conformance

Approvals	C-Tick, CE, CUL listed, UL listed
-----------	-----------------------------------

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

InRow RD, 300mm, Air Cooled, 220-240V, 50Hz | ACRD101 | Downloaded on 02/17/2021 (EST)

Conformance	
Standard warranty	1 year (parts only), 1 year on-site repair or replace with factory authorized Start-Up

  

General	
Air Discharge Patterns	Horizontal
Air Flow	1080.76lps
Compressor Type	Scroll
Intake Air	Rear return

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.