



InRow SC, 300mm, Air Cooled, Self-contained 200-240v 50Hz

ACSC101

Call for More Information +855-23-964-311

- Includes: Exhaust duct kit, Installation guide, Operations and maintenance manual

Input	
Input frequency	50 Hz +/- 3 Hz
Input Connections	IEC 60309 16 A 2P + E
Number of Power Cords	1
Input Power	2390 Watts

Communications & Management	
Control panel	Multifunction LCD status and control console

Physical	
Maximum Height	1991MM, 199.1CM
Maximum Width	300MM, 30.0CM
Maximum Depth	1069MM, 106.9CM
Rack Height	42U
Net Weight	165.92KG
Shipping weight	273.18KG
Shipping Height	2156MM, 215.6CM
Shipping Width	762MM, 76.2CM
Shipping Depth	1138MM, 113.8CM
Color	Black

Environmental	
Storage Temperature	0 - 40 °C

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Environmental	
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 4572meters
Audible noise at 1 meter from surface of unit	80.0dBA

Conformance	
Approvals	BSMI, C-Tick, CE, EN 55022 class A, FCC part 15 class A, GOST, ICES-003, UL listed, VCCI, VDE
Standard warranty	1 year (parts only), 1 year on-site repair or replace with factory authorized Start-Up

Sustainable Offer Status	
RoHS	Compliant

General	
Air Discharge Patterns	Horizontal
Air Flow	566.34lps
Amp Draw In-Rush	65.0A
Compressor Type	Rotary
Intake Air	Rear return
Refrigerant Charge	1.36pounds

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.